



CSB-10 /CSB-10T /CSB-10A Surface Mount Speakers

Features

- 10W passive - 10W active
- 3" full range transducer
- 70V, 100V, 6Ω

CSB-10, CSB-10T and CSB-10A are design and compact speakers for background music and speech. They are respectively low impedance passive, high impedance passive (70V, 100V) and active speaker, offering alternative for most installations.

The three models are equipped with a 3" full range transducer. Their output delivers 10W whatever the speaker type. The passive versions features grip connector terminals at the back, with a power tap selector for 70/100V model. The inputs of the active model are available on stereo RCA connectors, the signal being transformed in mono before to be amplified. A balanced 6.3 mm jack is also available as mono input connected in parallel to a link jack for daisy chain amplification. Made of ABS resin the cabinet is scratch and shock resistant. Of modern design, all models are available in black or white and are suitable for most decors. A rotatable mounting bracket is supplied for easy mounting on wall.



Specifications

MODEL	CSB-10	CSB-10T	CSB-10A
Speaker Type	Passive	Passive with transformer	Active
Transducer	1 x 3" full range speaker	1 x 3" full range speaker	1 x 3" full range speaker
SPL (1W/1m)	85dB (+/-3dB)	85dB (+/-3dB)	85dB (+/-3dB)
Power Rating	10W	70V: 1.25, 2.5, 5, 10W 100V: 10, 20, 40W	10W
Frequency Response	160Hz ~ 20kHz	160Hz ~ 20kHz	160Hz ~ 20kHz
Rated Impedance	6Ω	70V: 4kΩ, 2kΩ, 1kΩ, 500Ω 100V: 4kΩ, 2kΩ, 1kΩ	4Ω
Connector	Wiring terminal	Wiring terminal	Input: RCA / 6.3 mm jack balanced Output link: 6.3 mm jack
External Controls		Power selecting switch	Volume control / Power Switch
Power Supply	N/A	N/A	220-240V / 50 Hz; 110-220V / 60Hz
Color	Black / White	Black / White	Black / White
Dimensions (W x D x H)	115 x 107 x 175 mm (4.5" x 4.2" x 6.9")	115 x 107 x 175 mm (4.5" x 4.2" x 6.9")	115 x 107 x 175 mm (4.5" x 4.2" x 6.9")
Weight	0.52kg (1.2 lbs.)	0.9kg (2 lbs.)	1.06kg (2.4 lbs.)

Specifications subject to modification without notice



SEIKAKU TECHNICAL GROUP LIMITED

NO.1 LANE 17, SEC.2, HAN SHI WEST ROAD, TAICHUNG 40151 TAIWAN

Tel: +886-4-22313737 Fax: +886-4-22346757 www.seikaku.hk