



MPA-30H

Multiplex P.A. Amplifier

Features

- 30 W
- 4Ω - 25 /70/ 100V Outputs
- 2 Mic + 1 Aux/Phono Inputs
- Priority mode
- MP3 Player
- 12 V DC operation



The MPA-30H is a P.A. amplifier specifically designed for commercial applications. It is an ideal solution for bars, restaurants, retail outlets, office building, and other applications where paging and background music are required. The MPA-30H combines a 30 W amplifier with a three inputs mixer; it is a versatile and easy operating paging system. Two microphone inputs are available with TRS 6.35 mm jacks on the front panel. A selectable AUX/ PHONO input makes easy the connection to an outside stereo source. An insert out/in is available to connect signal processing devices, like delay units, EQs or anti-feedback systems. The output section accepts 4 Ω impedance loads and 25/70/100V line on barrier strip connector. A priority function is activated with the MIC1 input. The MPA-30H features a MP3 player for BGM or messages broadcast. A jumper makes access to an insert Out/In for the connection of signal processing devices like EQs or anti-feedback systems. The MPA-30R can also operate with a 12 V DC power supply.

Specifications

Power (RMS, 4Ω)	30W (AC) - 23W (DC 12V)
Power Consumption	60W (AC) - 45W (DC 12V))
Frequency Response	80Hz - 18kHz ± 3 dB
Power Supply	AC:115V ~ 230V 50/60Hz switching DC: 12V
Input Sensitivity	MIC 1~2 (6.3mm jack) unbalanced -50dBv /1kHz AUX (RCA) -6dBv /1kHz PHONO -50dBv /1kHz
THD & N (1 kHz - rated power)	<0.5%
S/N ratio	MIC 1~2 > 65 dB AUX > 75 dB PHONO > 55 dB
Outputs	4Ω - 25 /70 /100V
Controls	Volume x 3, Bass, Treble, Master
BGM module	MP3-300 player, SD /MMC /USB interface
Dimension (W x D x H)	280 x 190 x 75 mm (19" x .7.5" x 12.2")
Weight	4.5 kg (10 lbs)

Specifications subject to modification without notice



SEIKAKU TECHNICAL GROUP LIMITED

NO.1 LANE 17, SEC.2, HAN SHI WEST ROAD,TAICHUNG 40151 TAIWAN

Tel: +886-4-22313737 Fax: +886-4-22346757 www.seikaku.hk