



OWL-15A

Active Speaker

Features

- 250 W Active
- 15" Woofer + 1" Neodymium Driver
- 90° H x 60° V coverage
- 14.5 kg (29.1 lbs.)

OWL-15A is an active speaker dedicated to mobile applications. Made of polypropylene and featuring a built-in Class-D amplifier, the system is light and compact while delivering 250W.

The cabinet features a 15" woofer plus a 1" neodymium driver coupled to a 90°H x 60°V horn.

All settings are located on the rear panel including the power switch, the volume control, the ground lift and a "contour" switch. A combo XLR/ ¼" jack makes easy the connection to a microphone or line signal, plus a pair of RCA for a stereo source. A blank plate covers a space for an optional MP3 or Bluetooth module.



Specifications

Power Amplification	Class-D 250W Continuous (200W L + 50W HF), 500W Peak (400W LF + 100W HF)
Maximum SPL @ 1m	118dB Continuous / 121dB Peak
Frequency Response	62Hz – 19kHz (-3dB)
Frequency Range	50Hz – 20kHz (-10dB)
Transducer Low	15" (380mm) Woofer, 2" (50mm) Voice Coil
Transducer High	Neodymium Driver , 1" (25mm) Exit with 1" (25mm) Voice Coil
Horn Coverage (H x V)	90° x 60°, nominal (-6dB)
Crossover	2.5kHz
Connectors	1 x Line/Mic Female XLR-1/4" combo-RCA L/R inputs, 1 x Loop-Out Male XLR
External Controls	Volume, Power Switch with LED Indicator, Clip/Limit LED, Ground Lift, Contour On/Off, Mp3 Module Option
Protection	Thermal , Overload, Limiter, Compressor
Power Supply	AC-220/240V or AC-110/120 Volt, with Switching Power Mode, 50/60Hz
Enclosure Construction	Trapezoidal with Floor Monitor Capability / Injection-molded Polypropylene Enclosure; Perforated steel grille.
Mounting information	Integrated Pole Socket (36mm diameter); 3 handles; 4 M10 Threaded Sockets (2 top, 2 bottom)
Dimensions (H x W x D)	631 x 386 x 372 mm (24.8" x 15.2" x 14.6")
Weight (Net/Shipping)	14.5 kg (32.0 lbs.) / 17.0 kg (37.5 lbs.)

Specifications subject to modification without notice

Control Panel



Optional modules



SEIKAKU TECHNICAL GROUP LIMITED

NO.1 LANE 17, SEC.2, HAN SHI WEST ROAD, TAICHUNG 40151 TAIWAN

Tel: +886-4-22313737 Fax: +886-4-22346757 www.seikaku.hk

2018 V.1