



CSB-20 /CSB-20A /CSB-40A Surface Mount Speakers

Features

- 20W / 40W active
- 20W passive 6Ω
- 3" / 4" full range transducer

CSB-20, CSB-20A and CSB-40A are design and compact speakers for background music and speech. They are respectively low impedance passive and active speakers, offering alternative for most installations.

The speakers are equipped with a 3" or 4" full range transducer. Their output delivers 20W or 40W depending on the model. The passive version features grip connector terminals at the back. The inputs of the active models are available on stereo RCA connectors, the signal being transformed in mono before to be amplified. A mono input and a mono link output are available on 6.3 mm jack. Made of ABS resin the cabinet is scratch and shock resistant. Of modern design, all models are available in black or white and are suitable for most decors. A rotatable mounting bracket is supplied for easy mounting on wall.



Specifications

| MODEL | CSB-20 | CSB-20A | CSB-40A |
|------------------------|---|---|---|
| Speaker Type | Passive | Active | Active |
| Transducer | 1 x 3" full range speaker | 1 x 3" full range speaker | 1 x 4" full range speaker |
| SPL (1W/1m) | 85dB (+/-3dB) | 85dB (+/-3dB) | 90dB (+/-3dB) |
| Power Rating | 20W | 20W | 40W |
| Frequency Response | 132Hz ~ 20kHz | 132Hz ~ 20kHz | 88Hz ~ 18kHz |
| Rated Impedance | 6Ω | 4Ω | 4Ω |
| Connector | Wiring terminal | Input: RCA / 6.3 mm jack balanced Output link: 6.3 mm jack | Input: RCA / 6.3 mm jack balanced Output link: 6.3 mm jack |
| External Controls | | Volume control / Power Switch | Volume control / Power Switch |
| Power Supply | N/A | 220-240V / 50 Hz; 110-220V / 60Hz | 220-240V / 50 Hz; 110-220V / 60Hz |
| Color | Black / White | Black / White | Black / White |
| Dimensions (W x D x H) | 115 x 107 x 175 mm (4.5" x 4.2" x 6.9") | 115 x 107 x 175 mm (4.5" x 4.2" x 6.9") | 136 x 140 x 206 mm (5.35" x 5.51" x 8.11") |
| Weight | 0.8kg (1.78 lbs.) | 1.33kg (2.96 lbs.) | 2.0~2.4 kg (4.4~5.3 lbs.) |

Specifications subject to modification without notice



SEIKAKU TECHNICAL GROUP LIMITED

NO.1 LANE 17, SEC.2, HAN SHI WEST ROAD, TAICHUNG 40151 TAIWAN

Tel: +886-4-22313737 Fax: +886-4-22346757 www.seikaku.hk