



TA-506M PLUS

Multiplex P.A. Amplifier



Features

- 60 W
- 4Ω - 25 /70 /100V Outputs
- 4 Mic/Line + 1 Aux CDT/TAPE/TUNER Inputs
- 24 V DC operation

The TA-506M PLUS is a P.A. amplifier specifically designed for commercial applications. It is an ideal solution for bars, restaurants, retail outlets, office building, and other applications where speech and background music are required. It combines a 60 W amplifier with a five inputs mixer; it is a versatile and easy operating P.A. system.

Mono inputs are available on combo balanced XLR /TRS 6.35 mm jacks. A switch on each input selects a line or microphone level with a 24 V phantom power option.

The output section accepts 25/70/100 V constant voltage line and 4 Ω impedance loads. The TA-506M PLUS can also operate with a 24 V DC power supply.

Specifications

MODEL	TA-506M PLUS
Power Output	60W RMS / 90W MAX
Power Supply	AC:110V-120V 60Hz / 220-240V, DC: 24V
Frequency Response	50Hz - 15kHz ± 3 dB
Input / Sensitivity	MIC 1~4: (24V Phantom 1, 2, 3, 4) 600Ω, 0.5mV (-66dB) LINE / AUX: 200k Ω, 100mV (-22dB)
THD	<1%
S/N ratio	MIC 1~4 > 60 dB AUX > 70 dB
Output Impedance	4Ω
High Voltage Output	25 /70 /100V
Tone Control	Bass: ± 10dB at 100Hz, Treble: ± 10dB at 10kHz
Dimension (W x D x H)	420 x 280 x 88 mm (16.5" x .11" x 3.5")
Weight	7.8 kg (17.2 lbs)

Specifications subject to modification without notice



SEIKAKU TECHNICAL GROUP LIMITED

NO.1 LANE 17, SEC.2, HAN SHI WEST ROAD, TAICHUNG 40151 TAIWAN

Tel: +886-4-22313737 Fax: +886-4-22346757 www.seikaku.hk